

Model	730ZT	731ZT
Sensitivity (mV/m/s <sup>2</sup> )	1.0±10%	10.0±10%
Transverse Sensitivity (max)	< 5%	
Noise Floor (max)	< 20µVrms	< 40µVrms
Operating Temperature range	-50 deg C to 120 deg C	-50 deg C to 110 deg C
Frequency Response (±3dB)	0.5Hz to 15kHz (X, Y), 0.5Hz to 20kHz (Z)	0.5Hz to 10kHz (X, Y), 0.5Hz to 18kHz (Z)
Resonance Frequency	> 55kHz (Z)	
Measurement Range (m/s <sup>2</sup> )	±5,000	±450
Max. operational shock (m/s <sup>2</sup> )	< 30,000	
Output Impedance	< 100ohm	< 500ohm
Ground	Case ground	
Cables	Proprietary cable	
Connector	CZ664	
Material	Titanium	
Dimension (W × H × D)	10mm × 10mm × 10mm (Connector excluded)	
Weight	Approx. 4.4g	
Standard Accessories	Mounting screw (M3 × 0.5 × 4) 1 pc. Mount base (ABS resin, 19mm × 19mm) 1 pc. Proprietary cable CL-730B (3m, 4P-BNC) 1 pc.	